



PRODUCT INFORMATION

Dry Filter Cleaner

For Swimming Pools and Spas

Cure for clogged, contaminated filters

Proper filtration and chemical treatment are equally important in maintaining good pool water quality. **Dry Filter Cleaner** is a unique proprietary blend of multiple dry acid and nonionic surfactant formulation designed to rapidly remove oils, grease, dirt and minerals from both pool and spa cartridge and sand filters. Filters kept clean using this product will maintain the original filtering efficiency of your filter unit.

BENEFITS

- ✓ Returns filter to its optimum efficiency – Removes scale, rust, oil etc. which act to reduce filter efficiency.
- ✓ Minimizes cloudy water due to clogged filter - Removes grease, body oils and suntan lotions which collect in the filter.
- ✓ Reduces odors caused by contaminated filters – Removes organic deposits that cause odors.
- ✓ Maximizes volume of water filtered – Periodic use of **Dry Filter Cleaner** reduces maintenance costs by promoting better filtration, lengthening filter cycles and prolonging life of filter.

DIRECTIONS FOR USE FOR D.E. AND CARTRIDGE FILTERS

- ✓ Remove the filter cartridges or removable D.E. elements and rinse with water.
- ✓ Add 1 pound of Dry Filter Cleaner per 5 gallons of warm water in a plastic bucket, make enough solution to cover the filter elements.
- ✓ Stir solution with a wooden or plastic stirrer until it is completely dissolved, place the cartridge or element in this cleaner solution and soak 10 to 12 hours.
- ✓ Remove cartridge or elements from the solution and rinse with water using a high pressure nozzle. If possible, allow cartridge to dry before placing back.

DIRECTIONS FOR SAND FILTER AND NON-REMOVABLE ELEMENTS

- ✓ Prepare enough solution to cover filter media by dissolving 1 pound Dry Filter cleaner per 5 gallons of warm water.
- ✓ After back-washing the filter, turn off the pump, drain filter and remove all debris from lint pot.
- ✓ Turn pump back on with the handle still in the backwash position and pour solution into the lint pot until the sand and elements are completely covered.
- ✓ Shut off pump and leave handle in backwash position, allow solution to remain in the filter for 10 to 12 hours.
- ✓ Backwash until water exiting the line is completely clear, however do not allow cleaning solution to backwash into the pool.

AVAILABILITY

Filter Cleaner is available in a 2.25 lb package.

THE INFORMATION AND RECOMMENDATIONS MADE HEREIN ARE BASED UPON ALLCHEM INDUSTRIES WATER TREATMENT GROUP, INC. BEST KNOWLEDGE AND EXPERIENCE, AND ARE BELIEVED TO BE RELIABLE. SUCH INFORMATION AND RECOMMENDATIONS, HOWEVER, DO NOT CONSTITUTE A WARRANTY, AND NO PATENT LIABILITY CAN BE ASSUMED. THIS PUBLICATION IS NOT TO BE TAKEN AS A LICENSE TO OPERATE OR INFRINGE ON ANY PATENTS. SINCE ALLCHEM INDUSTRIES, INC. HAS NO CONTROL OVER THE CONDITIONS UNDER WHICH THE PRODUCT IS TRANSPORTED, STORED, HANDLED, USED OR APPLIED, BUYER MUST DETERMINE THE SUITABILITY OF THE PRODUCT FOR HIS PURPOSES. ALLCHEM INDUSTRIES, INC.'S LIABILITY ON ANY BASIS IS LIMITED TO THE PRICE OF THE PRODUCT USED.