



## PRODUCT INFORMATION

# Metal Out Plus

## For Swimming Pools

### Controls iron staining and scale formation

Dissolved metals and minerals (such as iron, calcium, manganese and magnesium) in pool water and corrosion of metal pool fittings will often cause staining and/or scaling. **Metal Out Plus** is an aqueous solution of hydroxyethylidene-diphosphonic acid (HEDP) that is best used for metallic stain removal and prevention of hard water scaling. This product is used in swimming pools to reduce scale formation in pumps and pool heaters, to eliminate plugging of filters and to reduce iron staining.

Soluble metals can be inhibited from precipitation by sequestering/chelating agents that bind with the colored metal ion to keep it in solution. **Metal Out Plus** sequesters the material causing stains and scale and holds them in solution. Regular use of this product helps keep pool water clear and the pool walls and plumbing in good condition. Use of **Metal Out Plus** as part of the pool maintenance program will result not only in the control of scale, but also in the removal of existing deposits. This product is also highly effective as a rust-control agent.

### DIRECTIONS FOR USE

- ✓ Maintain pool water in the pH range of 7.2 to 7.6, total alkalinity at 100 to 150 ppm and calcium hardness at 100 to 275 ppm. If pH falls below 7.0, serious corrosion problems may result.
- ✓ For best results, use **Metal Out Plus** in the evening with the pool pump and filter operating overnight.
- ✓ Add sixteen (16) ounces of **Metal Out Plus** per 10,000 gallons of water by premixing into plastic pail of water and then dispensing solution at deep end of the pool.
- ✓ Cloudiness accompanied by white flakes may appear indicating that the product is working, the cloudiness will eventually disappear.

### MAINTENANCE TREATMENT

- ✓ Follow all steps outlined above.
- ✓ Every 4-5 days, add two (2) ounces of **Metal Out Plus** per 10,000 gallons of pool water, to prevent stain and scale formation.

**Note:** In hard water areas where calcium hardness exceeds 300 ppm, it is advisable to double the dosages listed above. However, DO NOT increase the dosages more than double for one application.

### AVAILABILITY

**Metal Out Plus** is available in 1 quart bottles.

THE INFORMATION AND RECOMMENDATIONS MADE HEREIN ARE BASED UPON ALLCHEM INDUSTRIES WATER TREATMENT GROUP, INC. BEST KNOWLEDGE AND EXPERIENCE, AND ARE BELIEVED TO BE RELIABLE. SUCH INFORMATION AND RECOMMENDATIONS, HOWEVER, DO NOT CONSTITUTE A WARRANTY, AND NO PATENT LIABILITY CAN BE ASSUMED. THIS PUBLICATION IS NOT TO BE TAKEN AS A LICENSE TO OPERATE OR INFRINGE ON ANY PATENTS. SINCE ALLCHEM INDUSTRIES, INC. HAS NO CONTROL OVER THE CONDITIONS UNDER WHICH THE PRODUCT IS TRANSPORTED, STORED, HANDLED, USED OR APPLIED, BUYER MUST DETERMINE THE SUITABILITY OF THE PRODUCT FOR HIS PURPOSES. ALLCHEM INDUSTRIES, INC.'S LIABILITY ON ANY BASIS IS LIMITED TO THE PRICE OF THE PRODUCT USED.